



PRODUCT DECLARATION

SOUND ABSORPTION AREA FOR OBJECT

Measured and evaluated according to ISO 354 and ISO 20189


Producer:	Offecct
Object:	Soundwave® Scrunch
Size [mm]:	w=60 h=585 d=585

**Equivalent sound absorption area per unit
(m² Sabine)**

f(Hz)	1/3 Octave Band	Octave Band
50	0.00	
63	0.01	
80	0.01	
100	0.01	
125	0.02	0.03
160	0.06	
200	0.06	
250	0.10	0.10
315	0.14	
400	0.18	
500	0.24	0.23
630	0.29	
800	0.29	
1000	0.31	0.30
1250	0.32	
1600	0.34	
2000	0.34	0.35
2500	0.34	
3150	0.33	
4000	0.34	0.35
5000	0.36	

N₁₀ = 42

Equivalent sound absorption area per unit



ORIGINAL TEST REPORT

DATE OF REPORT





PRODUCT DECLARATION


SOUND ABSORPTION COEFFICIENT FOR SURFACE

Measured and evaluated according to ISO 354 and ISO 11654

Producer:	Offecct
Object:	Soundwave® Scrunch
Size [mm]:	w=60 h=585 d=585

Sound absorption coefficient

f(Hz)	1/3 Octave Band (α_s)	Octave Band (α)	Practical sound absorption coefficient (α_p)
50	0.04		
63	0.05	0.03	0.05
80	0.01		
100	0.06		
125	0.07	0.09	0.10
160	0.14		
200	0.17		
250	0.30	0.30	0.30
315	0.42		
400	0.53		
500	0.68	0.67	0.65
630	0.81		
800	0.85		
1000	0.89	0.88	0.90
1250	0.91		
1600	0.93		
2000	0.92	0.92	0.90
2500	0.92		
3150	0.91		
4000	0.89	0.91	0.90
5000	0.93		



ORIGINAL TEST REPORT

DATE OF REPORT

